

WELD ON TWO SPEED SQUARE TUBE JACK



TJD2SP-25100-F



- Improved interior design that enhances operation of jack.
- Heavy duty cross shaft weldment and brass bushings for durability and superior lift
- Eased/bevel on shaft end eliminates sharp metal edge
- Two speed model comes standard with handle and handle mounting hardware
- Two speed model includes a welded belly band on the bottom of the outer tube for additional strength to perform those heavy duty applications
- Durable black powder coat finish on inner and outer tubes
- Comes standard with grease zerks for easy greasing of jack
- Drop leg adds 13.75" of additional adjustability

LANDING GEAR SYSTEM

Product Code	Support Capacity (lbs)	Lift Capacity (lbs)	Handle Style	Travel Distance	Jack Height (fully retracted)	Total Adjust.	Description	Unit Weight (lbs)
TJD2SP-25100-F	25,000	25,000	Sidewind	12.5"	26.5"	25.5"	Pin to front, handle and mounting hardware	105.25
TJD-25100-F	25,000	25,000	Sidewind	12.5"	26.5"	25.5"	Pin to front, single speed companion jack when used in tandem, handle not included	81.75
TJD2SPSET-50100-F	50,000 Total (25,000/leg)	50,000 Total (25,000/leg)	Sidewind	12.5	26.5"	25.5"	Includes TJDSP-25100-F and TJD-25100-F above	187