

# D-Rings / Safety Chain

All chain assemblies below are overall length including the hook(s)



RRING-Q6000



DR-120B



DR-120W



DR-580W



DR-340W



DR-1034W



Grade 30  
Proof Coil



Grade 43 and  
Grade 70

Ram Part Number	Description
<b>D-rings and Safety Chains</b>	
RRING-Q6000	6000# pull capacity/ultimate break strength, 2000# work load, bolt on, square mounting holes, 3/8" d ring material size, 4.5"x5" bracket size, zinc
RRING-R6000	R6000: 6000# pull capacity/ultimate break strength, 2000# work load, round mounting holes, bolt on, 3/8" d ring material size, 4.5"x5" bracket size, zinc
DR-1034W	1" diameter D-Ring, w/weld on mounting bracket, forged from C1045 steel, I.D. 3"x4", U.B.S. 46760 lbs, S.W.L. 15586 lbs
DR-340W	3/4" diameter D-Ring, w/weld on mounting bracket, forged from C1045 steel, I.D. 3"x3", U.B.S. 26500 lbs, S.W.L. 9120 lbs
DR-580W	5/8" diameter w/weld-on mounting bracket, forged from C1045 steel, I.D. 3"x3", U.B.S. 18390 lbs, S.W.L. 6130 lbs
DR-120W	1/2" diameter D-Ring, w/weld-on mounting bracket, forged from C1045 steel, I.D. 2-1/2"x2-3/8", U.B.S. 12000 lbs, S.W.L. 4080 lbs
DR-120B	1/2" diameter D-Ring, forged from C1045 steel, with 2-Hole mounting bracket I.D. 2-1/2"x2-3/8", U.B.S. 11780 lbs, S.W.L. 4080 lbs, zinc
SC31624	3/16" x 24" safety chain, 3500# cap., 1 heat treated S-hooks, w/ safety latch, zinc plated, Grade 30 proof coil
SC31627	3/16" x 27" safety chain, 3500# cap., 1 heat treated S-hooks, w/ safety latch, zinc plated, Grade 30 proof coil
SC31648	3/16" x 48" safety chain, 3500# cap., 2 heat treated S-hooks, w/ safety latch, zinc plated, Grade 30 proof coil
SC1427	1/4" x 27" safety chains, 5200# cap., 1 heat treated S-hook, w/safety latch, zinc plated, Grade 30 proof coil
SC1436	1/4" x 36" safety chains, 5200# cap., 1 heat treated S-hook, w/safety latch, zinc plated, Grade 30 proof coil
SC1448	1/4" x 48" safety chains, 5200# cap., 2 heat treated S-hooks, w/ safety latch, zinc plated, Grade 30 proof coil
SC1454	1/4" x 54" safety chains, 5200# cap., 2 heat treated S-hooks, w/ safety latch, zinc plated, Grade 30 proof coil
SC1460	1/4" x 60" safety chains, 5200# cap., 2 heat treated S-hooks, w/ safety latch, zinc plated, Grade 30 proof coil
SC113230	5/16" x 30" safety chains, 7600# cap. 1 heat treated S-Hook, w/safety latch, zinc plated, Grade 30 proof coil
SC113254	5/16" x 54" safety chains, 7600# cap. 1 heat treated S-Hook, w/safety latch, zinc plated, Grade 30 proof coil
SC1430-G43	1/4" x 30" safety chains, 7800# cap., 1 forged slip hook, w/ safety latch, zinc plated, Grade 43 proof coil
SC51635-G43	5/16" x 35" safety chains, 11700# cap. 1 forged slip hook, zinc plated, Grade 43 proof coil
SC3835-G43	3/8" x 35" safety chains, 16200# cap. 1 forged slip hook, zinc plated, G43 high test
SC3841-G43	3/8" x 41" safety chains, 16200# cap. 1 forged slip hook, zinc plated, Grade 43 proof coil
SC1436-G70	1/4" x 36" safety chains, 12600# cap., 1 forged slip hook, w/ safety latch, zinc plated, Grade 70 proof coil
SC3840-G70	3/8" x 40" safety chains, 26400# cap. 1 forged slip hook, zinc plated, Grade 70 proof coil
SC3835-G70	3/8" x 35" safety chains, 26400# cap. 1 forged slip hook, zinc plated, Grade 70 proof coil