



# **Product Catalog**

## **Jacks**

**(Information and links also available in product sections of website.)**

### **Jacks**

- Marine**
- A-Frame**
- A-Frame Accessories**
- Weld On Bracket**
- Pipe-mount**
- Weld On Square Tube**
- Stabilizer**
- Electric A Frame**

### **Replacement Parts**



## 1000lb Capacity Marine Jack



Ideal for use with boat, sport craft, snowmobile and other recreational trailers.

- 1,000lb Support/Lift Capacity
- Large 1/2" pull pin to activate the swivel mechanism
- Large grooved comfort handle to operate the jack
- Single bolt through design with large washer for side load support
- Durable clear zinc finish (2 1/8" outer tube construction)
- Bolt on hardware included to mount from 2"x2" to 3"x5" trailer frame
- Single 6" poly caster wheel
- 10" travel distance
- 24" jack height fully retracted
- 13-1/2" bracket height (from bottom of jack to center of swivel when fully retracted)
- MJ-1206B
- MJ-1206BBX Retail Boxed (available special order upon request)



## 1000lb Capacity Marine Jack (Weld On Version)



Ideal for use with boat, sport craft, snowmobile and other recreational trailers.

- 1,000lb Support/Lift Capacity
- Large 1/2" pull pin to activate the swivel mechanism
- Large grooved comfort handle to operate the jack
- Snap ring design with raw weld-on bracket
- Durable clear zinc finish (2 1/8" outer tube construction)
- Single 6" poly caster wheel
- 10" travel distance
- 24" jack height fully retracted
- 13-1/2" bracket height (from bottom of jack to center of swivel when fully retracted)
- MJ-1000W



## 1200lb Capacity Marine Jack



Ideal for use with boat, sport craft, snowmobile and other recreational trailers.

- 1,200lb Support/Lift Capacity
- Large 1/2" pull pin to activate the swivel mechanism
- Large grooved comfort handle to operate the jack
- Four bolt pin through design with large diamond shaped washer for side load support
- Durable clear zinc finish (2 1/8" outer tube construction)
- Bolt on hardware included to mount from 2"x2" to 3"x5" trailer frame
- Single 6" poly caster wheel
- 10" travel distance
- 24" jack height fully retracted
- 13-1/2" bracket height (from bottom of jack to center of swivel when fully retracted)
- MJ-1200B
- MJ-1200BBX Retail Boxed (available special order upon request)

[www.ramtrailerproducts.com](http://www.ramtrailerproducts.com)



## 1500lb Capacity Marine Jack



Ideal for use with boat, sport craft, snowmobile and other recreational trailers.

- 1,500lb Support/Lift Capacity
- Large 1/2" pull pin to activate the swivel mechanism
- Large grooved comfort handle to operate the jack
- Four bolt pin through design with large diamond shaped washer for side load support
- Durable clear zinc finish (2 1/4" outer tube construction)
- Bolt on hardware included to mount from 2"x2" to 3"x5" trailer frame
- Single 8" poly caster wheel
- 10" travel distance
- 26" jack height fully retracted
- 13-1/2" bracket height (from bottom of jack to center of swivel when fully retracted)
- MJ-1500B



[www.ramtrailerproducts.com](http://www.ramtrailerproducts.com)





## 1500lb Capacity Marine Jack (Dual Wheel)



Ideal for use with boat, sport craft, snowmobile and other recreational trailers.

- 1,500lb Support/Lift Capacity
- Large 1/2" pull pin to activate the swivel mechanism
- Large grooved comfort handle to operate the jack
- Four bolt pin through design with large diamond shaped washer for side load support
- Durable clear zinc finish (2 1/4" outer tube construction)
- Bolt on hardware included to mount from 2"x2" to 3"x5" trailer frame
- Dual 6" poly caster wheels
- 10" travel distance
- 26" jack height fully retracted
- 12-1/2" bracket height (from bottom of jack to center of swivel when fully retracted)
- MJ-1500B-DWL Bulk
- MJ-1500BBX-DWL Retail Boxed bolt on version available special order upon request

[www.ramtrailerproducts.com](http://www.ramtrailerproducts.com)



## 2500lb Capacity Marine Jack



Ideal for use with boat, sport craft, snowmobile and other recreational trailers.

- 2,500lb Support/Lift Capacity
- Large grooved comfort handle to operate the jack
- 2-1/4" outside square tube construction
- Grease zerk for easy greasing of jack
- Durable clear zinc finish
- Bolt on hardware included to mount from 2"x2" to 3"x5" trailer frame
- 15" travel distance
- 24-3/4" jack height fully retracted
- 7-1/4" bracket height (from bottom of jack to center of swivel when fully retracted)
- 3-3/4"x7-1/2" sand foot with drop leg adds 13-3/4" of adjustability
- MJSQ-2500B



[www.ramtrailerproducts.com](http://www.ramtrailerproducts.com)



## 5000lb Capacity Marine Jack



Ideal for use with larger boat trailers.

- 5,000lb Support/Lift Capacity
- Large grooved comfort handle to operate the jack
- 2-1/2" outside square tube construction
- Grease zerk for easy greasing of jack
- Durable clear zinc finish
- Bolt on application with 5" x 7 1/2" mounting plate for up to 6" tall trailer frames (four 1/2" bolts/nuts and two mounting straps for mounting to trailer frame included)
- 1/2" holes spaced in 1" increments
- 15" travel distance
- 24-3/4" jack height fully retracted, 53" fully extended
- 6" x 8" sand foot with drop leg adds 13-3/4" of adjustability
- MJSQ-5000B (available special order upon request)





## 2000lb Capacity Topwind A Frame Jack



For use with trailers with A-frame couplers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer and inner tubes (clear zinc model also available) (2 1/4" outer tube construction)
- Handle arm durable zinc finish
- TJA-2000-B 14" travel distance, 8.25" bracket height from bottom of jack to bolt flange, 21.25" jack height when fully retracted
- TJA-2000-Z 14" travel distance, 8.25" bracket height from bottom of jack to bolt flange, 21.25" jack height when fully retracted - clear zinc outer and inner tubes
- TJA-2001-B 14" travel distance, 5" bracket height from bottom of jack to bolt flange, 21.25" jack height when fully retracted
- TJA-2002-B 15" travel distance, 9.25" bracket height from bottom of jack to bolt flange, 24.25" jack height when fully retracted



## 2000lb Capacity Topwind A Frame Jack



For use with trailers with A-frame couplers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Round knob handle design
- Durable exterior grade black finish on outer and inner tubes (2 1/4" outer tube construction)
- Handle arm durable zinc finish
- TJA-2006-B 14" travel distance, 8.25" bracket height from bottom of jack to bolt flange, 21.25" jack height when fully retracted



## 2000lb Capacity Sidewind A Frame Jack



For use with trailers with A-frame couplers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer and inner tubes (2 1/4" outer tube construction)
- Handle arm durable zinc finish
- TJA-2000S / TJA-2001S-B 14.5" travel distance, 9.25" bracket height from bottom of jack to bolt flange, 25" jack height when fully retracted



## 2000lb Capacity Sidewind A Frame Jack (Exterior Gear Box Style)



For use with trailers with A-frame couplers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Grease zerk for easy greasing of jack
- Durable exterior grade black finish on outer and inner tubes (2 1/4" out tube construction)
- Handle arm durable zinc finish
- TJA-2100S-B 15" travel distance, 9.25" bracket height from bottom of jack to bolt flange, 23" jack height when fully retracted (available special order upon request)





## 5000lb Capacity Topwind A Frame Jack



For use with trailers with A-frame couplers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer and inner tubes (2 1/4" outer tube construction)
- Handle arm durable zinc finish
- TJA-5000-B 14" travel distance, 10.5" bracket height from bottom of jack to bolt flange, 21.25" jack height when fully retracted



## 5000lb Capacity Topwind A Frame Jack (Taller Version)



For use with trailers with A-frame couplers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- Durable exterior grade black finish on outer and inner tubes (clear zinc model also available) (2 1/4" outer tube construction)
- TJA-5000T-B 15" travel distance, 10" bracket height from bottom of jack to bolt flange, 22.75" jack height when fully retracted
- TJA-5000T-Z 15" travel distance, 10" bracket height from bottom of jack to bolt flange, 22.75" jack height when fully retracted – clear zinc outer and inner tubes



## 5000lb Capacity Sidewind A Frame Jack (Exterior Gear Box Style)



For use with trailers with A-frame couplers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer and inner tubes (2 1/4" outer tube construction)
- Handle arm durable zinc finish
- TJA-5000S-B 14.5" travel distance, 9" bracket height from bottom of jack to bolt flange, 25" jack height when fully retracted



## A Frame Jack Accessories



- For use with any RAM A-Frame Jack
- Durable zinc finish
  - Includes bolt and nyloc nut to secure to the bottom of an a-frame jack
  - Two weep holes in the bottom of the sand foot for water drainage
  - 2,000 lb capacity
  - 2-1/4" x 4-1/2" foot size
  - JF-99



- For use with any RAM A-Frame Jack
- Includes mounting clip assembly to secure to the bottom of an a-frame jack
  - 1.7" tall
  - 4-1/2" x 6-1/4" foot size
  - 2,000 lb capacity
  - JF-100-Z / JF-100-Z-1020 durable zinc finish
  - JF-100-B-1020 durable black powder coat finish



- For use with any RAM A-Frame Jack
- Includes mounting clip assembly to secure to the bottom of an a-frame jack
  - 8.5" tall
  - 4-1/2" x 6-1/4" foot size
  - 2,000 lb capacity
  - JF-101 durable zinc finish





# A Frame Jack Accessories (Continued)



- For use with 2K top wind RAM A-Frame Jacks
- Includes mounting clip assembly to secure to the bottom of an a-frame jack
  - 9.5" tall, five position adjustability
  - 5-1/4" diameter foot with weep holes for water drainage
  - 2,000 lb capacity
  - JF-1005H-Z durable zinc finish



- For use with any RAM A-Frame Jack
- Durable zinc finish
  - Includes mounting clip assembly to secure to the bottom of an a-frame jack
  - 6" wheel assembly
  - 1,200 lb capacity
  - JC-101 poly wheel construction (shown in photo)
  - JC-102 steel wheel construction



- Bottom Support Plate
- Raw finish to be welded on the underside of an a frame coupler
  - 2.29" hole for a frame jack outer tube to pass through when installing
  - Additional side load support for an a frame jack application
  - JSP-100



# 2000lb Capacity Topwind Weld On Jack



Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- Large 1/2" pull pin to activate the swivel mechanism
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
- Grease zerk for easy greasing of jack
- Deep seated snap ring for side load support and raw weld on bracket
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- TJB-2001-B 10" travel distance, 11" bracket height from bottom of jack to center of swivel mount, 16.75" jack height when fully retracted
- TJB-2001-Z 10" travel distance, 11" bracket height from bottom of jack to center of swivel mount, 16.75" jack height when fully retracted – zinc outer and inner tube
- TJB-2002-B 15" travel distance, 16" bracket height from bottom of jack to center of swivel mount, 22" jack height when fully retracted



## 2000lb Capacity Sidewind Weld On Jack



Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Large 1/2" pull pin to activate the swivel mechanism
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
- Grease zerk for easy greasing of jack
- Deep seated snap ring for side load support and raw weld on bracket
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- TJB-2001S-B 10" travel distance, 10" bracket height from bottom of jack to center of swivel mount, 17.75" jack height when fully retracted
- TJB-2002S-B 15" travel distance, 15.25" bracket height from bottom of jack to center of swivel mount, 22.75" jack height when fully retracted

**STRONG & RELIABLE**  
**RAM**  
"The Best Overall Value In The Industry"

## 2000lb Capacity Topwind Pipemount Jack



- Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.
- 3,000lb Support Capacity / 2,000lb Lift Capacity
  - Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
  - 9/16" pin and lanyard assembly affixed to the jack
  - Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
  - Grease zerk for easy greasing of jack
  - Includes a 2" raw round weld on mating pipe
  - 3-3/4"x7-1/2" welded on durable zinc sand foot
  - TJP-2001-B 10" travel distance, 11" bracket height from bottom of jack to center of swivel mount, 17" jack height when fully retracted
  - TJP-2002-B 15" travel distance, 16" bracket height from bottom of jack to center of swivel mount, 22" jack height when fully retracted

[www.ramtrailerproducts.com](http://www.ramtrailerproducts.com)





# 2000lb Capacity Sidewind Pipemount Jack



Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 3,000lb Support Capacity / 2,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- 9/16" pin and lanyard assembly affixed to the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
- Grease zerk for easy greasing of jack
- Includes a 2" raw round weld on mating pipe
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- TJP-2001S-B 10" travel distance, 10" bracket height from bottom of jack to center of swivel mount, 17.5" jack height when fully retracted
- TJP-2002S-B 15" travel distance



# 5000lb Capacity Topwind Pipemount Jack

"The Best Overall Value In The Industry"



Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- 9/16" pin and lanyard assembly affixed to the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
- Grease zerk for easy greasing of jack
- Includes a 2" raw round weld on mating pipe
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- TJP-5001-B 10" travel distance, 11" bracket height from bottom of jack to center of swivel mount, 17" jack height when fully retracted
- TJP-5002-B 15" travel distance, 16" bracket height from bottom of jack to center of swivel mount, 22" jack height when fully retracted

[www.ramtrailerproducts.com](http://www.ramtrailerproducts.com)



# 5000lb Capacity Sidewind Pipemount Jack



Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- 5/8" pin and lanyard assembly affixed to the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
- Grease zerk for easy greasing of jack
- Includes a 2" raw round weld on mating pipe
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- TJP-5001S-B 10" travel distance, 10" bracket height from bottom of jack to center of swivel mount, 17.5" jack height when fully retracted
- TJP-5002S-B 15" travel distance, 15.25" bracket height from bottom of jack to center of swivel mount, 22.75" jack height when fully retracted



# 8000lb Capacity Topwind Pipemount Jack

**Image to  
come**

Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- 5/8" pin and lanyard assembly affixed to the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)
- Grease zerk for easy greasing of jack
- Includes a heavy duty 3" raw round weld on mating pipe
- 6"x8" welded on durable zinc sand foot
- TJP-7001-B 10" travel distance – 10" bracket height from bottom of jack to center of swivel mount, 19.75" jack height when fully retracted (available special order jack upon request)
- TJP-7002-B 15" travel distance, 15.25" bracket height from bottom of jack to center of swivel mount, 24.25" jack height when fully retracted (available special order jack upon request)





# 8000lb Capacity Sidewind Pipemount Jack

**Image to  
come**

Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity

- Large grooved comfort handle to operate the jack

- 5/8" pin and lanyard assembly affixed to the jack

- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and foot (2 1/4" outer tube construction)

- Grease zerk for easy greasing of jack

- Includes a heavy duty 3" raw round weld on mating pipe

- 6"x8" welded on durable zinc sand foot

- TJP-7001S-B 10" travel distance – 10" bracket height from bottom of jack to center of swivel mount, 21.5" jack height when fully retracted (available special order jack upon request)

- TJP-7002S-B 15" travel distance, 15.25" bracket height from bottom of jack to center of swivel mount, 24.25" jack height when fully retracted (available special order jack upon request)



# 5000lb Capacity Topwind Square Tube Jack



Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/4" square outer tube construction
- Grease zerk for easy greasing of jack
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- Drop leg adds 13.75" of adjustability (TJD-5000 model)
- TJD-5000 15" travel distance, 25.25" jack height when fully retracted, drop leg direct weld version
- TJD-5000-FLB 15" travel distance, 24.75" jack height when fully retracted, fixed leg version (available special order upon request)
- TJDP-5000-FLB 15" travel distance, 15" bracket height from bottom of jack to center of swivel mount, 24.75" jack height when fully retracted, fixed leg pipe mount version (available special order upon request)



# 5000lb Capacity Sidewind Square Tube Jack



TJD-5000S



TJD-5100S

Ideal for use with ag, industrial, commercial, recreational and many other types of trailers.

- 5,000lb Support Capacity / 3,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/4" square outer tube construction
- Grease zerk for easy greasing of jack
- 3-3/4"x7-1/2" welded on durable zinc sand foot
- Drop leg adds 13.75" of adjustability (TJD-5000S model)
- TJD-5000S 15" travel distance, 24.5" jack height when fully retracted, drop leg direct weld version, top style similar to MJSQ-2500B marine jack
- TJD-5100S 15" travel distance, 24.5" jack height when fully retracted, drop leg direct weld version, dog house style top (available special order upon request)
- TJD-5000S-FLB 15" travel distance, 24.5" jack height when fully retracted, fixed leg version, dog house style top (available special order upon request)
- TJDP-5000S-FLB 15" travel distance, 15.75" bracket height from bottom of jack to center of swivel mount, 24.75" jack height when fully retracted, fixed leg pipe mount version, dog house style top



# 8000lb Capacity Topwind Square Tube Jack (Standard Series)



Ideal for use with ag, industrial, commercial, recreational, larger utility and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/2" square outer tube construction
- Grease zerk for easy greasing of jack
- 6"x8" welded on durable zinc sand foot
- Drop leg adds 13.75" of adjustability (TJD-7000 model and TJDP-7000-B)
- TJD-7000 15" travel distance, 25.25" jack height when fully retracted, drop leg direct weld version
- TJDP-7000-B 15" travel distance, 14.5" bracket height from bottom of jack to center of swivel mount, 25.5" jack height when fully retracted, drop leg pipe mount version (special order available upon request)
- TJDP-7000-FLB 15" travel distance, 16.5" bracket height from bottom of jack to center of swivel mount, 25.5" jack height when fully retracted, fixed leg pipe mount version (special order available upon request)



# 8000lb Capacity Sidewind Square Tube Jack (Standard Series)



Ideal for use with ag, industrial, commercial, recreational, larger utility and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/2" square outer tube construction
- Grease zerk for easy greasing of jack
- 6"x8" welded on durable zinc sand foot
- Drop leg adds 13.75" of adjustability (TJD-7000S and TJDP-7000S-B models)
- TJD-7000S 15" travel distance, 25.5" jack height when fully retracted, drop leg direct weld version
- TJDP-7000S-B 15" travel distance, 14.5" bracket height from bottom of jack to center of swivel mount, 25.5" jack height when fully retracted, drop leg pipe mount version
- TJDP-7000S-FLB 15" travel distance, 14.5" bracket height from bottom of jack to center of swivel mount, 25.5" jack height when fully retracted, fixed leg pipe mount version





# 8000lb Capacity Topwind Square Tube Jack (Select Series)



Ideal for use with ag, industrial, commercial, recreational, larger utility and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/4" square outer tube construction
- Grease zerk for easy greasing of jack
- 6"x8" welded on durable zinc drop leg sand foot
- Drop leg adds 13.75" of adjustability
- TJD-8000 15" travel distance, 25.25" jack height when fully retracted, drop leg version
- TJDA-8000 a frame mount version also available special order



# 8000lb Capacity Sidewind Square Tube Jack (Select Series)



Ideal for use with ag, industrial, commercial, recreational, larger utility and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/4" square outer tube construction
- Grease zerk for easy greasing of jack
- 6"x8" welded on durable zinc drop leg sand foot
- Drop leg adds 13.75" of adjustability
- TJD-8000S 15" travel distance, 25.5" jack height when fully retracted, drop leg version
- TJDA-8000S a frame mount version also available special order



# 8000lb Capacity Topwind Square Tube Jack (Select Series)



Ideal for use with ag, industrial, commercial, recreational, larger utility and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- Durable exterior grade finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/4" square outer tube construction
- Grease zerk for easy greasing of jack
- 6"x8" welded on durable zinc drop leg sand foot
- Drop leg adds 13.75" of adjustability
- A Frame style flange allows to bolt on to a trailer frame (8" from bottom of jack foot to bottom of flange when fully retracted)
- TJDA-8000 15" travel distance, 25.5" jack height when fully retracted, a frame bolt on flange available special order



# 8000lb Capacity Sidewind Square Tube Jack (Select Series)



Ideal for use with ag, industrial, commercial, recreational, larger utility and many other types of trailers.

- 8,000lb Support Capacity / 7,000lb Lift Capacity
- Large grooved comfort handle to operate the jack
- Durable exterior grade black finish on outer tube and clear zinc finish on inner tube and drop leg foot
- 2-1/4" square outer tube construction
- Grease zerk for easy greasing of jack
- 6"x8" welded on durable zinc drop leg sand foot
- Drop leg adds 13.75" of adjustability
- A Frame style flange allows to bolt on to a trailer frame (8" from bottom of jack foot to bottom of flange when fully retracted)
- TJDA-8000S 15" travel distance, 25.5" jack height when fully retracted, a frame bolt on flange available special order





# 12000lb Capacity Sidewind Square Tube Jack (Standard Series)



Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 12,000lb Support Capacity / 10,000lb Lift Capacity
- Direct weld single speed side wind jack
- Durable exterior grade black finish
- 4" square outer tube construction
- Grease zerks for easy greasing of jack
- 8"x8" welded on durable drop leg sand foot
- Large octagon bushings on gear shaft for better function
- Drop leg adds 13.75" of adjustability
- TJD-12000SP-F2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware spring return drop leg jack
- TJD-12000SP-F2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, without handle assembly spring return drop leg jack
- TJD-12000SP-R2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, handle/handle clip and handle mounting hardware spring return drop leg jack
- TJD-12000SP-R2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, without handle assembly spring return drop leg jack
- TJD-12000-F2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware non-spring return drop leg jack
- TJD-12000-F2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, without handle assembly non-spring return drop leg jack
- TJD-12000-R2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment), pin to right, handle/handle clip and handle mounting hardware non-spring return drop leg jack
- TJD-12000-R2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, without handle assembly non-spring return drop leg jack





# 12000lb Capacity Sidewind Square Tube Two Speed Jack



Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 12,000lb Support Capacity / 10,000lb Lift Capacity
- Direct weld two speed side wind jack
- Two speed gear box is within the width of the outer tube to eliminate interference issues at the front of the trailer
- Durable exterior grade black finish
- 4" square outer tube construction
- Grease zerks for easy greasing of jack
- 8"x8" welded on durable drop leg sand foot
- Large octagon bushing on gear shaft for better function
- Drop leg adds 13.75" of adjustability
- TJD2SP-12900SP-F 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware spring return drop leg jack



# 12000lb Capacity Sidewind Square Tube Jack (12500 Series)

Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 12,000lb Support Capacity / 10,000lb Lift Capacity
- Direct weld single speed side wind jack
- Durable exterior grade black finish
- 4" square outer tube construction
- Grease zerks for easy greasing of jack
- 9"x9" welded on durable drop leg sand foot with weep holes for water drainage
- Large octagon bushings on gear shaft for better function
- Drop leg adds 13.75" of adjustability
- TJD-12500SP-F2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware spring return drop leg jack (available special order upon request)
- TJD-12500SP-F2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, without handle assembly spring return drop leg jack (available special order upon request)
- TJD-12500SP-R2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, handle/handle clip and handle mounting hardware spring return drop leg jack (available special order upon request)
- TJD-12500SP-R2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, without handle assembly spring return drop leg jack (available special order upon request)





# 12000lb Capacity Sidewind Square Tube Jack (Select Series)



Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 12,000lb Support Capacity / 10,000lb Lift Capacity
- Direct weld single speed side wind jack
- Durable exterior grade black finish
- 4" square outer tube construction
- Welded belly band on bottom of outer tube for added strength
- Grease zerks for easy greasing of jack
- 8"x8" welded on durable drop leg sand foot
- Large octagon bushings on gear shaft for better function
- Drop leg adds 13.75" of adjustability
- TJD-12020SP-F2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware spring return drop leg jack
- TJD-12020SP-F2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to front, without handle assembly spring return drop leg jack
- TJD-12020SP-R2 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, handle/handle clip and handle mounting hardware spring return drop leg jack
- TJD-12020SP-R2NH 12.5" travel distance, 28" jack height when fully retracted, 25.5" total adjustment, pin to right, without handle assembly spring return drop leg jack



# 12000lb Capacity Topwind Square Tube Jack



Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 12,000lb Support Capacity / 10,000lb Lift Capacity
- Direct weld single speed top wind jack
- Durable exterior grade black finish
- 4" square outer tube construction
- Grease zerk for easy greasing of jack
- 8"x8" welded on durable drop leg sand foot
- Drop leg adds 13.75" of adjustability
- TJD-12000TWSP-R 12.5" travel distance, 26" jack height when fully retracted, 25.5" total adjustment, pin to right, handle/handle clip and handle mounting hardware spring return drop leg jack





# 12000lb Capacity Topwind Square Tube Jack (Claw Handle)



Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 12,000lb Support Capacity / 10,000lb Lift Capacity
- Direct weld single speed top wind jack
- Durable exterior grade black finish
- Comfortable claw knob and clear zinc solid bar handle that can be folded away when not in use
- 4" square outer tube construction
- Grease zerk for easy greasing of jack
- 8"x8" welded on durable drop leg sand foot
- Drop leg adds 13.75" of adjustability
- TJD-12003TWSP-R 12.5" travel distance, 26" jack height when fully retracted, 25.5" total adjustment, pin to right, handle/handle clip and handle mounting hardware spring return drop leg jack (available special order upon request)





# 15000lb Capacity Sidewind Square Tube Jack

Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 15,000lb Support Capacity / 12,000lb Lift Capacity

- Direct weld single speed side wind jack

- Durable exterior grade black finish

- 4 3/8" square outer tube construction

- Grease zerks for easy greasing of jack

- 9"x9" welded on durable drop leg sand foot with weep holes for water drainage

- Large octagon bushings on gear shaft for better function

- Drop leg adds 13.75" of adjustability

- TJD-15000SP-F 12.5" travel distance, 28" jack height when fully retracted,

- 25.5" total adjustment, pin to front, handle/handle clip and handle

- mounting hardware spring return drop leg jack (available special order upon request)

- TJD-15000SP-R 12.5" travel distance, 28" jack height when fully retracted,

- 25.5" total adjustment, pin to right, handle/handle clip and handle

- mounting hardware spring return drop leg jack (available special order upon request)

- TJD2SP-15000SP-F two speed version



2 speed jack



# 20000lb Capacity Sidewind Dual Pin Square Tube Jack



2 speed jack



Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- Large dual pin foot release for easy activation of the spring return drop leg
- 20,000lb Support Capacity / 12,500lb Lift Capacity
- Direct weld single speed side wind jack
- Durable exterior grade black finish
- 4 3/8" square outer tube construction
- Grease zerks for easy greasing of jack
- 9"x9" welded on durable drop leg sand foot with weep holes for water drainage
- Large octagon bushings on gear shaft for better function
- Drop leg adds 13" of adjustability
- TJDDP-20000SP-F 13.5" travel distance, 29.5" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware spring return drop leg jack
- TJDDP2SP-20000SP-F two speed version



# 25000lb Capacity Sidewind Dual Square Tube Jack



2 speed jack

Ideal for use with commercial, construction, larger utility and many other types of trailers where heavy duty lifting is needed.

- 25,000lb Support Capacity / 25,00lb Lift Capacity
- Direct weld single speed side wind jack
- Durable exterior grade black finish
- 4 3/8" square outer tube construction
- Grease zerks for easy greasing of jack
- Drop leg adds 13.75" of adjustability
- TJD-25100-F 12.5" travel distance, 26.5" jack height when fully retracted, 25.5" total adjustment, pin to front, handle/handle clip and handle mounting hardware spring return drop leg jack
- TJD2SP-25100-F two speed version

# Stabilizer Jacks



Flip down stabilizer jack is ideal for all types of RV, utility and cargo trailers.

- 1,000 lb support capacity/650 lb lift capacity
- Adjustable from 11-1/2" to 17-3/4" vertical height
- Handle included with every two stabilizer jacks
- Black painted finish
- SJ-100 Flip Down Stabilizer Jack
- SJ-100-HD Handle (if extra handles are needed)



Telescopic stabilizer jack is ideal for cargo and industrial type trailers for corner stabilizing.

- 2,000 lb support capacity
- 20" durable zinc inner square tube allows multiple height adjustments
- 8" weldable raw 1-1/2" outer tube
- 5-1/4" diameter foot with weep holes for water drainage
- Includes a snap pin for easy and quick adjusting of jack
- SJ-R208 Telescopic Jack (bulk)
- SJ-R208-CTN Telescopic Jack (carton quantities)



Telescopic stabilizer jack is ideal for cargo and industrial type trailers for corner stabilizing.

- 5,000 lb support capacity
- 20" and 29" durable zinc inner square tube models available that allow for multiple height adjustments
- 13" weldable raw 2" outer tube
- 4" x 7 1/2" sand foot
- Includes a snap pin for easy and quick adjusting of jack
- SJ2-2013 Telescopic Jack (bulk) with 20" inner tube available special order upon request
- SJ2-2913 Telescopic Jack (bulk) with 29" inner tube available special order upon request



Scissor stabilizer jack is ideal for travel and 5th wheel trailers.

- 5,000 lb support capacity (in tandem)
- Adjustable from 4" to 24" vertical height
- Bearing set on crank side for longer jack life
- Eight slotted holes on top jack plate for mounting adjustability
- Black painted finish
- TJSC-24 Scissor Jack (handle sold separately)
- TJSC-24-HD Handle Assembly



# Electric Jacks



EJ-3520 model

For use with travel trailers, cargo and other types with a frame couplers.

- Easy to operate with just a flip of the switch
- Durable exterior grade black outer tube and zinc inner tube
- Zinc finish inner tube with removable sand foot
- 18" travel length
- Includes drop leg for 7-1/2" of additional adjustment
- Bright LED light for easy night time hookup
- Durable hardened steel gears for years and of normal use
- Crank handle for manual override in case of power loss
- Setup for use with a 12 volt RV/Marine deep cycle battery (battery not provided)
- 57" single wire to hook up to trailer battery (self grounding unit)
- EJ-3520-BBX 3500 lb lift capacity black housing retail boxed
- EJ-3520-WBX 3500 lb lift capacity white housing retail boxed



EJ-3550 model

For use with travel trailers, cargo and other types with a frame couplers.

- Easy to operate with just a flip of the switch
- Durable exterior grade black outer tube and zinc inner tube
- Zinc finish inner tube with removable sand foot
- 18" travel length
- Includes drop leg for 7-1/2" of additional adjustment
- Bright LED light for easy night time hookup
- Durable hardened steel gears for years and of normal use
- Crank handle for manual override in case of power loss
- Setup for use with a 12 volt RV/Marine deep cycle battery (battery not provided)
- Two 57" wires to hook up to trailer battery and grounding wire
- EJ-3550-BBX 3500 lb lift capacity black housing retail boxed
- EJ-3550-WBX 3500 lb lift capacity white housing retail boxed



EJ-3575 model

For use with travel trailers, cargo and other types with a frame couplers.

- Easy to operate with just a flip of the switch
- Durable exterior grade black outer tube and zinc inner tube
- Zinc finish inner tube with removable sand foot
- 18" travel length
- Includes drop leg for 7-1/2" of additional adjustment
- Bright LED light for easy night time hookup
- Durable hardened steel gears for years and of normal use
- Crank handle for manual override in case of power loss
- Setup for use with a 12 volt RV/Marine deep cycle battery (battery not provided)
- Two 57" wires to hook up to trailer battery and grounding wire
- Includes remote control
- EJ-3575-BBX 3500 lb lift capacity black housing retail boxed (available special order upon request)







## Jack Replacement Parts

See website links below as it will have most current information.

<https://ramtrailerproducts.com/wp-content/uploads/2024/12/Marine-Jack-Replacement-Parts-Dec-2024.pdf>

<https://ramtrailerproducts.com/wp-content/uploads/2024/12/A-Frame-Jack-Replacement-Parts-Dec-2024.pdf>

<https://ramtrailerproducts.com/wp-content/uploads/2024/12/Weld-On-Bracket-and-Pipe-Mount-Round-Tube-Jack-Replacement-Parts-Dec-2024.pdf>

<https://ramtrailerproducts.com/wp-content/uploads/2024/12/5K-and-7K-Square-Tube-Jack-Replacement-Parts-Dec-2024.pdf>

<https://ramtrailerproducts.com/wp-content/uploads/2024/12/12K-Square-Tube-Jack-Replacement-Parts-Dec-2024.pdf>

<https://ramtrailerproducts.com/wp-content/uploads/2024/12/Electric-Jack-Replacement-Parts-Dec-2024.pdf>